

ROMA INSULATION SYSTEMS

---

Proven quality.  
New surface finish.

---

Quick-assembly insulating panel  
with wood finish, type M

SO EVERYTHING FITS. **ROMA**

# Properties, technical data, product overview

ROMA is a leading manufacturer of wall and roof sandwich panel elements for industrial and cold-store construction.

We develop, manufacture and market complete systems for industrial construction engineering as well as cold-store and deep-freeze cell and cell-door construction. Climate test chambers, cleanrooms, and specialized climate-control applications are also part of our product portfolio. We have over 65 years of success and experience in highly specialized construction sectors. Ever since its founding, our family-run company has always manufactured top-quality products Made in Germany.

## Approval

General approval based on building authority/building law for use in walls/roofs. Approval Z-10.4-487 in accordance with DIN EN 14509 (CE marking) and approval Z-10.4-549 of DIBt, Berlin.

## Planning details

Please consult our most recent technical data sheets for detailed planning specifications.

[www.roma-daemmsysteme.de/downloads](http://www.roma-daemmsysteme.de/downloads)

ROMA type-M quick assembly insulating panels are now available in two different wood-effect finishes – Golden Oak and now also Dark Zebrano. Thanks to its high-quality surface finish, the facade element with concealed fitting and an effective width of 1000mm offers an attractive facing solution while keeping costs in mind.

And best of all: You can order a surface area of only 50m<sup>2</sup> and still count on rapid delivery of the panels of your choice.

Both surface finishes are also available for wall types P, FP and FV. Contact the ROMA sales team for more information about this product.



## Product properties

Hue Dark Zebrano

Hue Golden Oak

## Facade element M panel

Element width	1050mm
Module/effective width	1000mm
Available lengths	Up to 20000mm, depending on panel thickness
Custom sizes	On request
Insulating thicknesses	60, 80, 100, 120, 140, 170mm
Coating thickness	approx. 35 µm
Mirror gloss 60°	approx. 20 or according to pattern
Corrosion resistance	RC 3
UV resistance	RUV 3
Temperature resistance	- 20 °C to +80 °C
Scratch resistance	<= 20N

This information is non-binding and prepared to the best of our knowledge while taking relevant standards and regulations into consideration. Drawings and pictures serve informational purposes only. All rights reserved. Reproduction in whole or in part only by consent of Romakowski GmbH & Co. KG, Buttenwiesen, Germany. Our General Business Conditions (AGB) also apply.



For more information,  
please visit our website:  
[www.roma-daemmsysteme.de](http://www.roma-daemmsysteme.de)

## Romakowski GmbH & Co. KG

Herdweg 31  
86647 Buttenwiesen, Germany  
Phone +49 (0) 8274.999-0  
Fax +49 (0) 8274.999-150  
[info@roma-daemmsysteme.de](mailto:info@roma-daemmsysteme.de)